

## The ProView™ 60 Head Mounted Display System

---



- Full Color True VGA Resolution
- 100% Overlap
- Autosense Logic for Stereoscopic or Monoscopic Viewing
- Hi-Fi Stereo Sound
- “Comfort-Fit” Headband
- Eyeglass Compatible
- Ruggedized for Durability
- Full Range of Adjustments
- Hi Contrast and Brightness

The Display Products Group of KEO introduces the ProView 60, a 60 degree field of view HMD. This display device has the highest resolution available using liquid crystal displays, making the ProView™ lightweight and versatile for many simulation and training applications. Clear, crisp imagery offers virtual environment training a more realistic experience. It's full range of adjustments provide easy and fatigue-free viewing. Specially designed optics allow for hours of viewing without eye strain. The control unit is capable of accepting one or two VGA inputs, allowing versatility in monoscopic or true stereoscopic viewing.

### The Applications

---

- Virtual Environments
- Simulation & Training
- Augmented Reality
- Command & Control
- 3D Visualization
- Flight Training
- Portable Computing
- Computer Training
- CAD/CAM Display



## The ProView™ 60's Specifications

<b>DISPLAY</b>	Type LCD Resolution/Eye Brightness Contrast	2 full color, active matrix TFT, high speed polysilicon LCDs (2) - (640 x 3) x 480 4.5 arcmin/color group 25 foot lamberts 25:1
<b>OPTICAL</b>	Field of View Transmission Optics Eye Relief Exit Pupil Overlap Stereo/Mono	60° diagonal - 36° (V) x 48° (H) Non see through Plastic aspheric lens - independent optical paths for each eye Eyeglasses compatible, 20 mm Non pupil forming 100% Yes
<b>MECHANICAL</b>	IPD IPD Range HMD Weight Headtracker	Readily accessible on each display module Meets 95th percentile male/female adult 30 ounces Accommodates either Polhemus or Ascension sensor
<b>CONTROL UNIT</b>	Video Inputs  Horizontal Scan Rate(F <sub>H</sub> ) Vertical Scan Rate Genlocked Inputs Cable Length Video Outputs Controls Indicators (LED) Connectors  Power	One or two VGA 640 x 480, H&V - TTL, analog 0.7V P-P, 75 ohms, 60 Hz video inputs Autosense for stereoscopic or monoscopic operation Internal and external sync 31.5 kHz 60.0 Hz Independent phased locked loops for left and right eye 20 feet 2 VGA video loops to display monitor Audio adjust:mono control Power on/off Video in VGA, 15 pin DA, female, (video in) 2 VGA, 15 pin DA, female, (video out for monitor) 2 BNC barrel connectors, RGB H&V, (video in) 2 sets RCA connectors, (stereo audio com pass through) 2 (cables are not provided to either video or audio connectors) 120 VAC, 60 Hz, or 240 VAC, 50 Hz, 25W (power cable included)

Display Products Group  
Kaiser Electro-Optics, Inc.  
2752 Loker Avenue West, Carlsbad, CA 92008  
T: 760.438.9255 F: 760.438.6875 e-mail: info@keo.com